

IAL3Ex HQSS



Termination set in shrink technology for application in hazardous area.

Termination Set Ex



- Compact design
- Temperature resistant up to 180°C
- Flexible usage
- Different sets separately available
- Applicable for: ILH...CF/Qx , ILS...NF/Qx

Description

The IAL3Ex HQSS contains a very flexible and space saving termination set and is used in hazardous areas.

The usage of a special temperature resistant FEP-Connection cable grants different application possibilities at very high temperatures.

This set is composed of connection and end seal parts. These are also separately available.



Technical Data

Temperature Resistant up to: 180°C
 For Heating Tapes: ILH, ILS...NF/Qx
 Length Connection Side: 140mm
 Length End Seal: ca. 55mm

Ordering Information

Part number:
 IAL3Ex HQSS: Power connection and end seal in a set.

Approval

ATEX, IECEx, EAC

Alternative Products

Part number:
 IAL4SS: Ex-termination set for direct entry

Marking

II 2G Ex mb IIC T3
 II 2D Ex mb IIIC T200°C

Additional Products

Part number:
 AG 101 Ex: Ex-enclosure for up to 3 heating circuits
 (for different versions view enclosure datasheet)
 ALF 25: Heat resistant FEP-Supply cable
 3Gx2.5mm²

Further Information

Please consult the installation instructions!